


SRLED LIGHTS
www.srledlights.com

SR-009

MR-16

Ceiling Recessed Adjustable



Specifications

Product Reference

Model No

SR-009

Installation Type

Recessed

Beam Direction

Fixed

Construction & Materials

Housing Material

Aluminium Die Cast

Heatsink

Passive Cooled Aluminium

Finish

White Powder Coated

IP Rating

IP-20

Physical

Diameter

50mm

Recessed Depth

55mm

Light Technology

Binning

3 step MacAdam

LED Life Time

> 50,000 Hours

Colour Rendering CRI

CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics

metalized reflector

Beam Direction

Fixed

Electrical System

Input Voltage

220V-240V AC/50Hz

Input Power

9W

Power Factor

>0.95

ATHD

<20%

Driverphilips(Constant -
Current Led Driver)

Controls

Standard

Switchable On/Off

Optional

Phase Cut / Analog / Dali Dimming

CCT Tunable

Available on Request

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SR-009

MR-16

Ceiling Recessed Non Adjustable

SR - 009 09w

LED Fitted

CREE COB LED 36Vdc/200mA

Co-Related Colour Temperature

3000K 4000K 6000K

Delivered Lumens

810

Efficacy (System - lm/watt)

90

Beam Angle

15° / 24° / 38° / 60°

LED Power Watts

8

System Power Watts

9

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Next to Laghu Udyog , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 022-26860670



SR

LED LIGHTS
www.srledlights.com