

SR-131 LED Spot Light Series Ceiling Recessed Adjustable



Specifications

Product Reference

Model No SR-131 Installation Type Recessed Beam Direction Fixed Trimless

Light Technology

Binning 3 step MacAdam LED Life Time > 50, 000 Hours Colour Rendering CRI CRI80 as standard/ CRI90 on Request

Controls

Standard Switchable On/Off Optional Phase Cut / Analog / Dali Dimming CCT Tunable Available on Request

Construction & Materials

Housing Material Aluminium Die Cast Heatsink Passive Cooled Aluminium Finish White Powder Coated IP Rating IP-20

Optics

Secondary Optics Optical Lens Beam Direction Fixed Trimless

Physical

Diameter 101mm Cutout Diameter 101mm Recessed Depth 90mm

Electrical System

Input Voltage 220V-240V AC/50Hz Input Power 13W Power Factor >0.95 ATHD <20% Driver Philips (Constant -Current Led Driver)



www.srledlights.com



SR-131

LED Spot Light Series Ceiling Recessed Adjustable

<u>SR - 131 13w</u>

LED Fitted CREE COB LED 36Vdc/300mA

Co-Related Colour Temperature 2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens 1040

Efficacy (System - Im/watt) 80

Beam Angle 38°

LED Power Watts

System Power Watts 13

S.R.Industries GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate , Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com Tel.No : 022-26860670

