

SRLED LIGHTS
www.srledlights.com

SR-082

LED Spot Light Series
Ceiling Recessed non Adjustable


SR.082



OPTIONAL REFLECTOR



WHITE GOLD



Specifications

Product Reference

Model No
SR-082

Installation Type
Recessed

Beam Direction
Fixed

Construction & Materials

Housing Material
Aluminium Die Cast

Heatsink
Passive Cooled Aluminium

Finish
White Powder Coated

IP Rating
IP-20

Physical

Diameter
75mm x 45mm

Cutout Diameter
68mm x 37mm

Recessed Depth
49mm

Light Technology

Binning
3 step MacAdam

LED Life Time
> 50,000 Hours

Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics
metalized reflector

Beam Direction
Fixed

Electrical System

Input Voltage
220V-240V AC/50Hz

Input Power
4w

Power Factor
>0.95

ATHD
<20%

Driver
SR MAKE (Constant - Current Led Driver)

Controls

Standard
Switchable On/Off

Optional
Phase Cut / Analog / Dali Dimming

CCT Tunable
Available on Request

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SR-082

LED Spot Light Series
Ceiling Recessed Non Adjustable

SR - 082 4w

LED Fitted

CREE COB LED 36Vdc/700mA

Co-Related Colour Temperature

3000K 4000K 6000K

Delivered Lumens

320

Efficacy (System - lm/watt)

80

Beam Angle

15° / 24° / 38° / 60°

LED Power Watts

3.5

System Power Watts

4

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Next to Laghu Udyog , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 022-26860670



SR

LED LIGHTS
www.srledlights.com