


LED Spot Light Series SURFACE lights Adjustable





Specifications

Product Reference

Model No SR-138 Installation Type SURFACE Beam Direction adjustable

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics metalized reflactor Beam Direction adjustable

Physical

Diameter 52mm Body lenth 125mm Base lenth 30mm Total height 160mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
13W/15W
Power Factor
>0.95
ATHD
<20%
Driver
philips (Constant Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
available on Request





LED Spot Light Series SURFACE lights Adjustable

SR - 138 13w/15w

LED Fitted

CREE COB LED 36Vdc/300mA/350ma

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

1170/1350

Efficacy (System - Im/watt)

90

Beam Angle

15° / 24° / 38° / 60°

LED Power Watts

11.5/13

System Power Watts

13/15

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

