


LED Spot Light Series

Ceiling Recessed Adjustable





Specifications

Product Reference

Model No SR-038 Installation Type Recessed Beam Direction

Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Construction & Materials

Housing Material Aluminium Die Cast Heatsink Passive Cooled Aluminium Finish

White Powder Coated IP Rating IP-20

Optics

Secondary Optics
metalized reflactor
Beam Direction
Fixed
Reflactor colour option
rose gold,gold,chrome,white,black

Physical

Diameter 85mm Cutout Diameter 75mm Recessed Depth 75mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
13W
Power Factor
>0.95
ATHD
<20%
Driver
philips (Constant Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request





LED Spot Light Series

Ceiling Recessed Non Adjustable

SR - 038 13w

LED Fitted

CREE COB LED 36Vdc/300mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

1170

Efficacy (System - Im/watt)

90

Beam Angle

15° / 24° / 38° / 60°

LED Power Watts

11.5

System Power Watts

13

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

