




## **LED Spot Light Series**

Ceiling Recessed non Adjustable





## **Specifications**

## **Product Reference**

**Model No** SR-134 Installation Type Recessed **Beam Direction** Fixed

# **Light Technology**

**Controls** 

Binning 3 step MacAdam **LED Life Time** > 50, 000 Hours **Colour Rendering CRI** CRI80 as standard/ CRI90 on Request

Standard Switchable On/Off Optional Phase Cut / Analog / Dali Dimming **CCT Tunable** Available on Request

## **Construction & Materials**

**Housing Material** Diameter Aluminium Die Cast 85MM Heatsink **Cutout Diameter** Passive Cooled Aluminium 75MM Finish **Recessed Depth** White Powder Coated 105MM **IP Rating** 

## **Optics**

IP-20

**Secondary Optics** metalized reflactor **Beam Direction** Fixed

# **Electrical System**

**Physical** 

Input Voltage 220V-240V AC/50Hz **Input Power** 15W **Power Factor** >0.95 ATHD <20% Driver BAG (Constant -Current Led Driver)





## **LED Spot Light Series**

Ceiling Recessed Non Adjustable

### SR - 134 15w

### **LED Fitted**

CREE COB LED 36Vdc/350mA

### **Co-Related Colour Temperature**

2700K 3000K 3500K 4000K 5000K 6500K

### **Delivered Lumens**

1200

## Efficacy ( System - Im/watt)

80

### **Beam Angle**

15° / 24° / 38° / 60°

### **LED Power Watts**

13

### **System Power Watts**

15

# S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

