

SRE-084

LED Spot Light Series

Ceiling Recessed non Adjustable





Specifications

Product Reference

Model No SRE-084 Installation Type TRIMLESS Beam Direction Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics Optical Lens Beam Direction Fixed

Physical

Diameter 70mm Cutout Diameter 45mm Recessed Depth 59mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
9w
Power Factor
>0.95
ATHD
<20%
Driver
SR MAKE (Constant Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
not available





SR LED LIGHTS www.srledlights.com

LED Spot Light Series

Ceiling Recessed Non Adjustable

SRE - 083 9w

LED Fitted

CREE COB LED 36Vdc/200mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

720

Efficacy (System - Im/watt)

80

Beam Angle

120°

LED Power Watts

7.5

System Power Watts

9

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

