


SRLED LIGHTS
www.srledlights.com

SR-141

LED Spot Light Series
Ceiling surface non Adjustable

Specifications

Product Reference

Model No
SR-141
Installation Type
surface
Beam Direction
Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50,000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
not available

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
Optical Lens
Beam Direction
Fixed

Physical

Diameter
136mm x 35mm
Recessed Depth
66mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
10W
Power Factor
>0.95
ATHD
<20%
Driver
Eaglerise (Constant -
Current Led Driver)

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SR-141

LED Spot Light Series
Ceiling surface non Adjustable

SR - 141 - 10W

LED Fitted

osram LED 18Vdc/600mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

800

Efficacy (System - lm/watt)

80

Beam Angle

45°

LED Power Watts

8.5

System Power Watts

10

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 022-26860670



SR

LED LIGHTS
www.srledlights.com