




## **LED Spot Light Series**

Ceiling Recessed Adjustable





## **Specifications**

## **Product Reference**

Model No SRE-041 Installation Type Recessed Beam Direction adjustable

# **Light Technology**

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

### **Controls**

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

## **Construction & Materials**

Housing Material Diameter
Aluminium Die Cast 108mm
Heatsink Cutout Diameter
Passive Cooled Aluminium 104mm
Finish Recessed Depth
White Powder Coated 120mm
IP Rating
IP-20

## **Optics**

Secondary Optics Optical Lens Beam Direction adjustable

# **Electrical System**

**Physical** 

Input Voltage
220V-240V AC/50Hz
Input Power
13W
Power Factor
>0.95
ATHD
<20%
Driver
philips (Constant Current Led Driver)





### **LED Spot Light Series** Ceiling Recessed Adjustable

#### SRE - 041 13w

#### **LED Fitted**

CREE COB LED 36Vdc/300mA

#### **Co-Related Colour Temperature**

2700K 3000K 3500K 4000K 5000K 6500K

#### **Delivered Lumens**

1040

## Efficacy ( System - Im/watt)

80

### **Beam Angle**

15° / 24° / 38° / 60°

#### **LED Power Watts**

11.5

#### **System Power Watts**

13

# S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

