


SR-129 LED Spot Light Series Ceiling surface NonAdjustable





### Specifications

# Product Reference

Model No SR-129 Installation Type surface Beam Direction fixed

#### Light Technology

Binning 3 step MacAdam LED Life Time > 50, 000 Hours Colour Rendering CRI CRI80 as standard/ CRI90 on Request

### **Controls**

Standard Switchable On/Off

# Construction & Materials

Housing Material Aluminium Die Cast Heatsink Passive Cooled Aluminium Finish White Powder Coated IP Rating IP-20

# **Optics**

Secondary Optics metalized reflactor Beam Direction fixed

# **Physical**

Diameter 95mm Height 125mm

#### Electrical System

Input Voltage 220V-240V AC/50Hz Input Power 20W Power Factor >0.95 ATHD <20% Driver fulham (Constant -Current Led Driver)





#### SR-129

LED Spot Light Series Ceiling surface NonAdjustable

#### <u>SR - 129 20w</u>

LED Fitted CREE COB LED 36Vdc/500mA

**Co-Related Colour Temperature** 2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens 1800

Efficacy ( System - Im/watt) 90

Beam Angle

LED Power Watts 18

System Power Watts 20

# S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate , Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com Tel.No : 022-26860670

