



LED Spot Light Series

Ceiling Recessed non Adjustable



Specifications

Product Reference

Model No SRE-015 Installation Type Recessed Beam Direction Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating

Optics

IP-20

Secondary Optics
Optical Lens
Beam Direction
Fixed

Physical

Diameter 22mm Cutout Diameter 16mm Recessed Depth 29mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
2w
Power Factor
>0.95
ATHD
<20%
Driver
SR MAKE (Constant Current Led Driver)





SRE-015

LED Spot Light Series

Ceiling Recessed Non Adjustable

SRE - 015 2w

LED Fitted

CREE COB LED 3.2 Vdc/700mA

Co-Related Colour Temperature

3000K

Delivered Lumens

160

Efficacy (System - Im/watt)

80

Beam Angle

10°

LED Power Watts

1

System Power Watts

2

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

