







Specifications

Product Reference

Model No SRE-031 Installation Type Trimless recessed Beam Direction adjustable

Light Technology

Binning 3 step MacAdam LED Life Time > 50, 000 Hours Colour Rendering CRI CRI80 as standard/ CRI90 on Request

Controls

Standard Switchable On/Off Optional Phase Cut / Analog / Dali Dimming CCT Tunable Available on Request

Construction & Materials

Housing Material Aluminium Die Cast Heatsink Passive Cooled Aluminium Finish White Powder Coated IP Rating IP-20

Optics

Secondary Optics metalized reflactor Beam Direction adjustable Trimless

Physical

Diameter 87mm Cutout Diameter 87mm Recessed Depth 95mm

Electrical System

Input Voltage 220V-240V AC/50Hz Input Power 12w Power Factor >0.95 ATHD <20% Driver BAG (Constant -Current Led Driver)



www.srledlights.com



SRE-031

LED Spot Light Series Ceiling Recessed Adjustable

SRE - 031 12w

LED Fitted CREE COB LED 36Vdc/250mA

Co-Related Colour Temperature 2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens 1080

Efficacy (System - Im/watt) 90

Beam Angle 15° / 24° / 38° / 60°

LED Power Watts 10.5

System Power Watts

S.R.Industries GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate , Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com Tel.No : 022-26860670

