
SR LED LIGHTS www.srledlights.com







Specifications

Product Reference

Model No SR-124 Installation Type Recessed Beam Direction adjustable

Light Technology

Binning 3 step MacAdam LED Life Time > 50, 000 Hours Colour Rendering CRI CRI80 as standard/ CRI90 on Request

Controls

Standard Switchable On/Off Optional Phase Cut / Analog / Dali Dimming CCT Tunable Available on Request

Construction & Materials

Housing Material Aluminium Die Cast Heatsink Passive Cooled Aluminium Finish White Powder Coated IP Rating IP-20

Optics

Secondary Optics Optical Lens Beam Direction adjustable

Physical

Diameter 68mm Cutout Diameter 58mm Recessed Depth 25mm

Electrical System

Input Voltage 220V-240V AC/50Hz Input Power 9W Power Factor >0.95 ATHD <20% Driver philips (Constant -Current Led Driver)



LED LIGHTS www.srledlights.com



SR-124

LED Spot Light Series Ceiling Recessed Adjustable

<u>SR - 124 9w</u>

LED Fitted CREE COB LED 36Vdc/200mA

Co-Related Colour Temperature 2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens 810

Efficacy (System - Im/watt) 90

Beam Angle 15° / 24° / 38° / 60°

LED Power Watts 8

System Power Watts 9

S.R.Industries GalaNo. 1 & 2, 1st Floor, Geeta Industrial Estate, Next to Laghu Udyog, I.B.Patel Road, Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com Tel.No : 022-26860670

