

SRLED LIGHTS
www.srledlights.com

SR-007

LED Spot Light Series
Ceiling Recessed non Adjustable

SR.007



Specifications

Product Reference

Model No
SR-007
Installation Type
Recessed
Beam Direction
Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
Optical Lens
Beam Direction
Fixed

Physical

Diameter
45mm
Cutout Diameter
39mm
Recessed Depth
75mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
5W
Power Factor
>0.95
ATHD
<20%
Driver
SR MAKE (Constant -
Current Led Driver)

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SR-007

LED Spot Light Series
Ceiling Recessed Non Adjustable

SR - 007 5w

LED Fitted

CREE COB LED 36Vdc/100mA

Co-Related Colour Temperature

3000K 4000K 6000K

Delivered Lumens

450

Efficacy (System - lm/watt)

90

Beam Angle

36°

LED Power Watts

4.5

System Power Watts

5

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Next to Laghu Udyog , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 022-26860670



SR

LED LIGHTS
www.srledlights.com