


**SR**LED LIGHTS  
www.srledlights.com

SR-123

LED down Light Series  
Ceiling Recessed non Adjustable

## Specifications

### Product Reference

**Model No**  
SR-123  
**Installation Type**  
Recessed  
**Beam Direction**  
Fixed

### Construction & Materials

**Housing Material**  
Aluminium Die Cast  
**Heatsink**  
Passive Cooled Aluminium  
**Finish**  
White Powder Coated  
**IP Rating**  
IP-20

### Physical

**Diameter**  
155mm  
**Cutout Diameter**  
147mm  
**Recessed Depth**  
35mm

### Light Technology

**Binning**  
3 step MacAdam  
**LED Life Time**  
> 50,000 Hours  
**Colour Rendering CRI**  
CRI80 as standard/ CRI90 on Request

### Optics

**Secondary Optics**  
diffused  
**Beam Direction**  
Fixed

### Electrical System

**Input Voltage**  
220V-240V AC/50Hz  
**Input Power**  
17W  
**Power Factor**  
>0.95  
**ATHD**  
<20%  
**Driver**  
philips (Constant -  
Current Led Driver)

### Controls

**Standard**  
Switchable On/Off  
**Optional**  
Phase Cut / Analog / Dali Dimming  
**CCT Tunable**  
Available on Request

**SR**LED LIGHTS  
www.srledlights.com



SR

LED LIGHTS  
www.srledlights.com

SR-123

LED down Light Series  
Ceiling Recessed Adjustable

**SR - 123 17w**

**LED Fitted**

BRIDLUX SMD LED 36Vdc/400mA

**Co-Related Colour Temperature**

2700K 3000K 3500K 4000K 5000K 6500K

**Delivered Lumens**

1190

**Efficacy ( System - lm/watt)**

70

**Beam Angle**

120°

**LED Power Watts**

15

**System Power Watts**

17

---

S.R.Industries  
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,  
Next to Laghu Udyog , I.B.Patel Road ,  
Goregaon (E), Mumbai - 400063.  
Email Id : sales@srledlights.com  
Tel.No : 022-26860670



SR

LED LIGHTS  
www.srledlights.com