



LED Spot Light Series

Ceiling Recessed non Adjustable







Specifications

Product Reference

Model No SR-036 Installation Type Recessed Beam Direction Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating

Optics

IP-20

Secondary Optics metalized reflactor Beam Direction Fixed

Physical

Diameter 80mm Cutout Diameter 70mm Recessed Depth 79mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
9W
Power Factor
>0.95
ATHD
<20%
Driver
philips (Constant Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request





LED Spot Light Series

Ceiling Recessed Non Adjustable

SR - 036 9w

LED Fitted

CREE COB LED 36Vdc/200mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

810

Efficacy (System - Im/watt)

90

Beam Angle

15° / 24° / 38° / 60°

LED Power Watts

8

System Power Watts

9

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

