


www.srledlights.com

SRE-058

LED Spot Light Series

Ceiling Recessed non Adjustable





Specifications

Product Reference

Model No SR-058 Installation Type Recessed Beam Direction Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI

CRI80 as standard/ CRI90 on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated

Optics

IP Rating IP-20

Secondary Optics metalized reflactor Beam Direction Fixed

Physical

Diameter 50mm x 50mm Cutout Diameter 55mm x 55mm Recessed Depth 75mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
7w
Power Factor
>0.95
ATHD
<20%
Driver
fulham (Constant -

Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request





SRE-058

LED Spot Light Series

Ceiling Recessed Non Adjustable

SRE - 058 7w

LED Fitted

CREE COB LED 36Vdc/150mA

Co-Related Colour Temperature

3000K 4000K 6000K

Delivered Lumens

630

Efficacy (System - Im/watt)

90

Beam Angle

38°

LED Power Watts

5.5

System Power Watts

7

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate , Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No: 022-26860670

