


SRE-071 LED Spot Light Series Ceiling Recessed non Adjustable





Specifications

Product Reference

Model No SR-071 Installation Type Recessed Beam Direction Fixed

Light Technology

Binning 3 step MacAdam LED Life Time > 50, 000 Hours Colour Rendering CRI CRI80 as standard/ CRI90 on Request

Controls

Standard Switchable On/Off Optional Phase Cut / Analog / Dali Dimming CCT Tunable Available on Request

Construction & Materials

Housing Material Aluminium Die Cast Heatsink Passive Cooled Aluminium Finish White Powder Coated IP Rating IP-20

<u>Optics</u>

Secondary Optics metalized reflactor Beam Direction Fixed

Physical

Diameter 243mm x 36mm Cutout Diameter 238mm x 28mm Recessed Depth 56mm

Electrical System

Input Voltage 220V-240V AC/50Hz Input Power 24w Power Factor >0.95 ATHD <20% Driver PHILIPS (Constant -Current Led Driver)





SRE-07

LED Spot Light Series Ceiling Recessed Non Adjustable

SRE - 071 24w

LED Fitted CREE COB LED 30Vdc/700mA

Co-Related Colour Temperature 3000K 4000K 6000K

Delivered Lumens 1680

Efficacy (System - Im/watt) 80

Beam Angle

LED Power Watts 21

System Power Watts 24

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate , Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com Tel.No : 022-26860670

