




LED Spot Light Series

Ceiling Recessed Adjustable





Specifications

Product Reference

Model No SRE-013 Installation Type Recessed Beam Direction adjustable pull out

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

Construction & Materials

Housing Material Diameter
Aluminium Die Cast 100mm
Heatsink Cutout Diameter
Passive Cooled Aluminium 92mm
Finish Recessed Depth
White Powder Coated 117mm
IP Rating
IP-20

Optics

Secondary Optics
Optical Lens
Beam Direction
adjustable pull out

Electrical System

Physical

Input Voltage
220V-240V AC/50Hz
Input Power
12W
Power Factor
>0.95
ATHD
<20%
Driver
BAG (Constant Current Led Driver)







LED Spot Light Series

Ceiling Recessed Non Adjustable

SRE - 013 12w

LED Fitted

CREE COB LED 36Vdc/250mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

1080

Efficacy (System - Im/watt)

90

Beam Angle

15° / 24° / 38° / 60°

LED Power Watts

10.5

System Power Watts

12

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

