

SR-197 LED Spot Light Series Ceiling surface NonAdjustable



Specifications

Product Reference

Model No SR-197 Installation Type surface Beam Direction fixed

Light Technology

Binning 3 step MacAdam LED Life Time > 50, 000 Hours Colour Rendering CRI CRI80 as standard/ CRI90 on Request

Controls

Standard Switchable On/Off

Construction & Materials

Housing Material Aluminium Die Cast Heatsink Passive Cooled Aluminium Finish White Powder Coated IP Rating IP-20

Optics

Secondary Optics OPTICAL LENS Beam Direction fixed

Physical

Diameter 80mm Height 95mm

Electrical System

Input Voltage 220V-240V AC/50Hz Input Power 12W Power Factor >0.95 ATHD <20% Driver SR MAKE (Constant -Current Led Driver)





SR-197

LED Spot Light Series Ceiling surface NonAdjustable

<u>SR - 197 12w</u>

LED Fitted CREE COB LED 36Vdc/250mA

Co-Related Colour Temperature 2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens 1080

Efficacy (System - Im/watt) 90

Beam Angle

LED Power Watts 10.5

System Power Watts 12

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate , Next to Laghu Udyog , I.B.Patel Road , Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com Tel.No : 022-26860670

