

SRE-069

LED Spot Light Series

Ceiling Recessed non Adjustable





Specifications

Product Reference

Model No SR-069 Installation Type Recessed Beam Direction Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics metalized reflactor Beam Direction Fixed

Physical

Diameter 82mm x 36mm Cutout Diameter 74mm x 28mm Recessed Depth 56mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
7w
Power Factor
>0.95
ATHD
<20%
Driver
PHILIPS (Constant -

Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
NOT AVAILABLE





SRE-069

LED Spot Light Series

Ceiling Recessed Non Adjustable

SRE - 069 7w

LED Fitted

CREE COB LED 9Vdc/700mA

Co-Related Colour Temperature

3000K 4000K 6000K

Delivered Lumens

560

Efficacy (System - Im/watt)

മറ

Beam Angle

38°

LED Power Watts

5.5

System Power Watts

7

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate , Next to Laghu Udyog , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063. Email Id : sales@srledlights.com

Tel.No: 022-26860670

