



Specifications

Product Reference

Model No
SR-082
Installation Type
Recessed
Beam Direction
Non Adjustable

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Physical

Diameter
75mm x 45mm
Cutout Diameter
68mm x 37mm
Recessed Depth
49mm

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50,000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics
Metalized Reflector
Beam Direction
Non Adjustable

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
4w
Power Factor
>0.95
ATHD
<20%
Driver
SR MAKE (Constant -
Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Not Available
CCT Tunable
Not Available



SR

LED LIGHTS
www.srledlights.com

SR-082

LED leaser Light Series
Ceiling Recessed Non Adjustable

SR - 082 4w

LED Fitted

Osram SMD 3030 LED 6Vdc/700mA

Co-Related Colour Temperature

3000K 4000K 6500K

Delivered Lumens

320

Efficacy (System - lm/watt)

80

Beam Angle

24°

LED Power Watts

3.5

System Power Watts

4

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Opp Hdfc Bank , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com