


**SR**LED LIGHTS  
www.srledlights.com

SR-150

LED Down Light Series  
Ceiling Recessed Adjustable开孔:  $\Phi 55$ **Specifications****Product Reference**

**Model No**  
SR-150

**Installation Type**  
Recessed

**Beam Direction**  
Adjustable

**Construction & Materials**

**Housing Material**  
Aluminium Die Cast

**Heatsink**  
Passive Cooled Aluminium

**Finish**  
White Powder Coated

**IP Rating**  
IP-20

**Physical**

**Diameter**  
62mm

**Cutout Diameter**  
55mm

**Recessed Depth**  
90mm

**Light Technology**

**Binning**  
3 step MacAdam

**LED Life Time**  
> 50,000 Hours

**Colour Rendering CRI**  
CRI80 as standard/ CRI90 on Request

**Optics**

**Secondary Optics**  
Optical Lens

**Beam Direction**  
Adjustable

**Electrical System**

**Input Voltage**  
220V-240V AC/50Hz

**Input Power**  
7W

**Power Factor**  
>0.95

**ATHD**  
<20%

**Driver**  
BAG Make (Constant - Current Led Driver)

**Controls**

**Standard**  
Switchable On/Off

**Optional**  
Phase Cut / Analog / Dali Dimming

**CCT Tunable**  
On Request

**SR**LED LIGHTS  
www.srledlights.com



SR

LED LIGHTS  
www.srledlights.com

SR-150

LED Down Light Series  
Ceiling Recessed Adjustable

**SR - 150**

**LED Fitted**

CREE COB LED 36Vdc/150mA

**Co-Related Colour Temperature**

2700K 3000K 3500K 4000K 5000K 6500K

**Delivered Lumens**

504

**Efficacy ( System - lm/watt)**

72

**Beam Angle**

15° / 24° / 38°

**LED Power Watts**

5.4

**System Power Watts**

7

---

S.R.Industries  
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,  
Opp. Hdfc Bank , I.B.Patel Road ,  
Goregaon (E), Mumbai - 400063.  
Email Id : sales@srledlights.com  
Tel.No : 9137899504



SR

LED LIGHTS  
www.srledlights.com