


SRLED LIGHTS
www.sriedlights.com**SRE-045****8° TO 36° Beam Adjustable Down Light**
Ceiling Recessed Non Adjustable

Specifications

Product Reference

Model No
SRE-045
Installation Type
Recessed
Beam Direction
8° TO 36° Beam Adjustable

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available On Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
Optical Lens
Beam Direction
Non Adjustable

Physical

Diameter
50mm
Cutout Diameter
45mm
Recessed Depth
65mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
7w
Power Factor
>0.95
ATHD
<20%
Driver
BAG (Constant -
Current Led Driver)

SRLED LIGHTS
www.sriedlights.com



SR

LED LIGHTS
www.srledlights.com

SRE-045

8° TO 36° Beam Adjustable Down Light
Ceiling Recessed Non Adjustable

SRE - 045 7w

LED Fitted

CREE COB LED 36Vdc/150mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

490

Efficacy (System - lm/watt)

70

Beam Angle

8° TO 36° Beam Adjustable

LED Power Watts

5.4

System Power Watts

7

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Opp Hdfc Bank , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com