


SRLED LIGHTS
www.srledlights.com**SRE-069****LED Leaser Light Series**
Ceiling Recessed Non Adjustable

Specifications

Product Reference

Model No
SR-069
Installation Type
Recessed
Beam Direction
Non Adjustable

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Not Available

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
Optical Lens
Beam Direction
Non Adjustable

Physical

Diameter
82mm x 36mm
Cutout Diameter
74mm x 24mm
Recessed Depth
56mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
7w
Power Factor
>0.95
ATHD
<20%
Driver
Philips (Constant -
Current Led Driver)

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SRE-069

LED Leaser Light Series
Ceiling Recessed Non Adjustable

SRE - 069 7w

LED Fitted

Osram 3030 Smd Led 9Vdc/700mA

Co-Related Colour Temperature

3000K 4000K 6500K

Delivered Lumens

455

Efficacy (System - lm/watt)

65

Beam Angle

38°

LED Power Watts

6.3

System Power Watts

7

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Opp Hdfc Bank , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com