


SRLED LIGHTS
www.srledlights.com**SRE-070****Led leaser Light Series**
Ceiling Recessed Non Adjustable

Specifications

Product Reference

Model No
SR-070

Installation Type
Recessed

Beam Direction
Non Adjustable

Construction & Materials

Housing Material
Aluminium Die Cast

Heatsink
Passive Cooled Aluminium

Finish
White Powder Coated

IP Rating
IP-20

Physical

Diameter
127mm x 36mm

Cutout Diameter
119mm x 28mm

Recessed Depth
56mm

Light Technology

Binning
3 step MacAdam

LED Life Time
> 50,000 Hours

Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics
Optical Lens

Beam Direction
Non Adjustable

Electrical System

Input Voltage
220V-240V AC/50Hz

Input Power
12w

Power Factor
>0.95

ATHD
<20%

Driver
Philips (Constant -
Current Led Driver)

Controls

Standard
Switchable On/Off

Optional
Phase Cut / Analog / Dali Dimming

CCT Tunable
Available on Request

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SRE-070

Led leaser Light Series
Ceiling Recessed Non Adjustable

SRE - 070 12w

LED Fitted

Osram 3030 Smd Led 15VDC/700mA

Co-Related Colour Temperature

3000K 4000K 6500K

Delivered Lumens

780

Efficacy (System - lm/watt)

65

Beam Angle

38°

LED Power Watts

10.5

System Power Watts

12

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Opp Hdfc Bank , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com