



SR

LED LIGHTS
www.srledlights.com

SRE-033

LED DOWN Light Series

Ceiling circle of lights



Specifications

Product Reference

Model No

SRE-033

Installation Type

trimless recessed / suspended / surface

Beam Direction

adjustable

Light Technology

Binning

3 step MacAdam

LED Life Time

> 50,000 Hours

Colour Rendering CRI

CRI80 as standard/ CRI90 on Request

Construction & Materials

Housing Material

Aluminium Die Cast

Heatsink

Passive Cooled Aluminium

Finish

black Powder Coated

IP Rating

IP-20

Optics

Secondary Optics

Optical Lens

Beam Direction

adjustable

Physical

Diameter

350mm / 650mm / 950mm

Electrical System

Input Voltage

220V-240V AC/50Hz

Input Power

30w / 60w / 90w

Power Factor

>0.95

ATHD

<20%

Driver

FULHAM (Constant -
Current Led Driver)

Controls

Standard

Switchable On/Off

Optional

Phase Cut / Analog / Dali Dimming

CCT Tunable

Available on Request



SR

LED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SRE-033

LED DOWN Light Series
Ceiling circle of lights

SRE - 033 30W/60W/90W

LED Fitted

CREE COB LED 37Vdc/700mA/1400ma/2100ma

Co-Related Colour Temperature

3000k

Delivered Lumens

2400/4800/7200

Efficacy (System - lm/watt)

80

Beam Angle

24°

LED Power Watts

26/52/78

System Power Watts

30/60/90

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Next to Laghu Udyog , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 022-26860670



SR

LED LIGHTS
www.srledlights.com