


SRLED LIGHTS
www.srledlights.com

SR-150

LED Down Light Series
Ceiling trimless Adjustable开孔: $\Phi 55$ **Specifications****Product Reference**

Model No
SR-150

Installation Type
trimless

Beam Direction
Adjustable

Construction & Materials

Housing Material
Aluminium Die Cast

Heatsink
Passive Cooled Aluminium

Finish
White Powder Coated

IP Rating
IP-20

Physical

Diameter
75mm

Cutout Diameter
55mm

Recessed Depth
75mm

Light Technology

Binning
3 step MacAdam

LED Life Time
> 50,000 Hours

Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics
Optical Lens

Beam Direction
Adjustable

Electrical System

Input Voltage
220V-240V AC/50Hz

Input Power
7W

Power Factor
>0.95

ATHD
<20%

Driver
BAG Make (Constant - Current Led Driver)

Controls

Standard
Switchable On/Off

Optional
Phase Cut / Analog / Dali Dimming

CCT Tunable
On Request

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SR-150

LED Down Light Series
Ceiling trimless Adjustable

SR - 150

LED Fitted

CREE COB LED 36Vdc/150mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

504

Efficacy (System - lm/watt)

72

Beam Angle

15° / 24° / 38°

LED Power Watts

5.4

System Power Watts

7

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Opp. Hdfc Bank , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com