


**SR**LED LIGHTS  
www.srledlights.com

SR-172

LED Down Light Series  
Ceiling trimless Adjustable开孔:  $\Phi$  70MM

## Specifications

### Product Reference

**Model No**  
SR-172

**Installation Type**  
trimless

**Beam Direction**  
Adjustable

### Construction & Materials

**Housing Material**  
Aluminium Die Cast

**Heatsink**  
Passive Cooled Aluminium

**Finish**  
White Powder Coated

**IP Rating**  
IP-20

### Physical

**Diameter**  
100mm

**Cutout Diameter**  
70mm

**Recessed Depth**  
75mm

### Light Technology

**Binning**  
3 step MacAdam

**LED Life Time**  
> 50,000 Hours

**Colour Rendering CRI**  
CRI80 as standard/ CRI90 on Request

### Optics

**Secondary Optics**  
Optical Lens

**Beam Direction**  
Adjustable

### Electrical System

**Input Voltage**  
220V-240V AC/50Hz

**Input Power**  
12W

**Power Factor**  
>0.95

**ATHD**  
<20%

**Driver**  
Fulham (Constant -  
Current Led Driver)

### Controls

**Standard**  
Switchable On/Off

**Optional**  
Phase Cut / Analog / Dali Dimming

**CCT Tunable**  
Available on Request

**SR**LED LIGHTS  
www.srledlights.com



SR

LED LIGHTS  
www.srledlights.com

SR-172

LED Down Light Series  
Ceiling trimless Adjustable

**SR - 172 12w**

**LED Fitted**

CREE COB LED 36Vdc/300mA

**Co-Related Colour Temperature**

2700K 3000K 3500K 4000K 5000K 6500K

**Delivered Lumens**

900

**Efficacy ( System - lm/watt)**

75

**Beam Angle**

15° / 24° / 38°

**LED Power Watts**

10.5

**System Power Watts**

12

---

S.R.Industries  
GalaNo. 1 & 2, 1st Floor, Geeta Industrial Estate ,  
Opp Hdfc Bank, I.B.Patel Road ,  
Goregaon (E), Mumbai - 400063.  
Email Id : sales@srledlights.com  
Tel No: 9137899504



SR

LED LIGHTS  
www.srledlights.com