


SRLED LIGHTS
www.srledlights.com

SRE-031

Led Down Light Series
Trimless Ceiling Recessed Adjustable

Specifications

Product Reference

Model No
SRE-031

Installation Type
Trimless Recessed

Beam Direction
Adjustable 350°

Construction & Materials

Housing Material
Aluminium Die Cast

Heatsink
Passive Cooled Aluminium

Finish
White Powder Coated

IP Rating
IP-20

Physical

Diameter
88mm

Cutout Diameter
88mm

Recessed Depth
92mm

Light Technology

Binning
3 step MacAdam

LED Life Time
> 50,000 Hours

Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics
Optical Lens

Beam Direction
Adjustable 350°

Electrical System

Input Voltage
220V-240V AC/50Hz

Input Power
12w

Power Factor
>0.95

ATHD
<20%

Driver
Fulham (Constant - Current Led Driver)

Controls

Standard
Switchable On/Off

Optional
Phase Cut / Analog / Dali Dimming

CCT Tunable
Available on Request

SRLED LIGHTS
www.srledlights.com**SR**

SRE-031

SRE - 031 10w

LED Fitted

CREE COB LED 36Vdc/250mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

1080

Efficacy (System - lm/watt)

90

Beam Angle

38°

LED Power Watts

10.5

System Power Watts

12

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Opp Hdfc Bank , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 9137899504