


**SR**LED LIGHTS  
www.srledlights.com**SRE-059****Led Down Light Series**  
Ceiling Trimless Non Adjustable

## Specifications

### Product Reference

**Model No**  
SRE-059  
**Installation Type**  
trimless  
**Beam Direction**  
Fixed

### Light Technology

**Binning**  
3 step MacAdam  
**LED Life Time**  
> 50,000 Hours  
**Colour Rendering CRI**  
CRI80 as standard/ CRI90 on Request

### Controls

**Standard**  
Switchable On/Off  
**Optional**  
Phase Cut / Analog / Dali Dimming  
**CCT Tunable**  
Available on Request

### Construction & Materials

**Housing Material**  
Aluminium Die Cast  
**Heatsink**  
Passive Cooled Aluminium  
**Finish**  
White Powder Coated  
**IP Rating**  
IP-20

### Optics

**Secondary Optics**  
metalized reflector  
**Beam Direction**  
Fixed

### Physical

**Diameter**  
96mm x 50mm  
**Cutout Diameter**  
100mm x 55mm  
**Recessed Depth**  
75mm

### Electrical System

**Input Voltage**  
220V-240V AC/50Hz  
**Input Power**  
14w  
**Power Factor**  
>0.95  
**ATHD**  
<20%  
**Driver**  
fulham (Constant -  
Current Led Driver)

**SR**LED LIGHTS  
www.srledlights.com



SR

LED LIGHTS  
www.srledlights.com

SRE-058

**Led Down Light Series**  
Ceiling Trimless Non Adjustable

**SRE - 059 14w**

**LED Fitted**

CREE COB LED 36Vdc/300mA

**Co-Related Colour Temperature**

3000K 4000K 6000K

**Delivered Lumens**

1260

**Efficacy ( System - lm/watt)**

90

**Beam Angle**

38°

**LED Power Watts**

12.5

**System Power Watts**

14

---

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 022-26860670



SR

LED LIGHTS  
www.srledlights.com