


SRLED LIGHTS
www.srledlights.com**SRE-061****Led Down Light Series**
Ceiling Trimless Non Adjustable

Specifications

Product Reference

Model No
SRE-061
Installation Type
trimless
Beam Direction
Fixed

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50,000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
metalized reflector
Beam Direction
Fixed

Physical

Diameter
190mm x 50mm
Cutout Diameter
197mm x 55mm
Recessed Depth
75mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
28w
Power Factor
>0.95
ATHD
<20%
Driver
fulham (Constant -
Current Led Driver)

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SRE-061

Led Down Light Series
Ceiling Trimless Non Adjustable

SRE - 061 21w

LED Fitted

CREE COB LED 36Vdc/600mA

Co-Related Colour Temperature

3000K 4000K 6000K

Delivered Lumens

2520

Efficacy (System - lm/watt)

90

Beam Angle

38°

LED Power Watts

26

System Power Watts

28

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Next to Laghu Udyog , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 022-26860670



SR

LED LIGHTS
www.srledlights.com