SR
LED LIGHTS
www.srledlights.com

SR-063

LED Down Light Series

Ceiling Recessed Adjustable



Specifications

Product Reference

Model No
SR-063
Installation Type
Recessed
Beam Direction
Adjustable

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Physical

Diameter
93mm
Cutout Diameter
70mm
Recessed Depth
100mm

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics
Metalized Reflactor
Beam Direction
Adjustable

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
12w
Power Factor
>0.95
ATHD
<20%
Driver
Fulham (Constant - Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

SR
LED LIGHTS
www.srledlights.com

SR - 063 12w

LED Fitted
CREE COB LED 36Vdc/300mA

Co-Related Colour Temperature
2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens
1080

Efficacy (System - lm/watt)
90

Beam Angle
45°

LED Power Watts
10.5

System Power Watts
12

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Opp Hdfc Bank , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 9137899504