

**SR**LED LIGHTS  
www.srledlights.com**SRE-053****Led Down Light Series**  
Ceiling Recessed Adjustable

## Specifications

### Product Reference

**Model No**  
SRE-053  
**Installation Type**  
Recessed  
**Beam Direction**  
Adjustable 350°

### Light Technology

**Binning**  
3 step MacAdam  
**LED Life Time**  
> 50,000 Hours  
**Colour Rendering CRI**  
CRI80 as standard / CRI90 on Request

### Controls

**Standard**  
Switchable On/Off  
**Optional**  
Phase Cut / Analog / Dali Dimming  
**CCT Tunable**  
Available on Request

### Construction & Materials

**Housing Material**  
Aluminium Die Cast  
**Heatsink**  
Passive Cooled Aluminium  
**Finish**  
White Powder Coated  
**IP Rating**  
IP-20

### Optics

**Secondary Optics**  
Optical Lens  
**Beam Direction**  
Adjustable 350°

### Physical

**Diameter**  
85mm  
**Cutout Diameter**  
75mm  
**Recessed Depth**  
90mm

### Electrical System

**Input Voltage**  
220V-240V AC/50Hz  
**Input Power**  
12W / 15W  
**Power Factor**  
>0.95  
**ATHD**  
<20%  
**Driver**  
Fulham (Constant -  
Current Led Driver)

**SR**LED LIGHTS  
www.srledlights.com



SR

LED LIGHTS  
www.srledlights.com

SRE-053

Led Down Light Series  
Ceiling Recessed Adjustable

**SRE - 053 12w/15W**

**LED Fitted**

CREE COB LED 36Vdc/300mA/350MA

**Co-Related Colour Temperature**

2700K 3000K 3500K 4000K 5000K 6500K

**Delivered Lumens**

936 / 1162

**Efficacy ( System - lm/watt)**

78

**Beam Angle**

15 / 24° / 36°

**LED Power Watts**

10.5 / 12.7

**System Power Watts**

12 / 15

---

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Opp Hdfc Bank , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 9137899504



SR

LED LIGHTS  
www.srledlights.com