


SRLED LIGHTS
www.srledlights.com**SRE-110****Led Spot Light Series**
Ceiling Recessed Adjustable

Specifications

Product Reference

Model No
SRE-110
Installation Type
Recessed
Beam Direction
Adjustable 350°

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Physical

Diameter
55mm
Cutout Diameter
50mm
Recessed Depth
174mm

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50,000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics
Optical Lens
Beam Direction
Adjustable 350°

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
9W
Power Factor
>0.95
ATHD
<20%
Driver
Fulham (Constant -
Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SRE-110

LED Spot Light Series
Ceiling Recessed Adjustable

SRE - 110 9w

LED Fitted

CREE COB LED 36Vdc/200mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

630

Efficacy (System - lm/watt)

70

Beam Angle

38°

LED Power Watts

7.5

System Power Watts

9

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Opp Hdfc Bank , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com