


SRLED LIGHTS
www.srledlights.com

SR-077

LED Down Light Series
Ceiling Recessed Non Adjustable

Specifications

Product Reference

Model No
SR-077

Installation Type
Recessed

Beam Direction
Non Adjustable

Construction & Materials

Housing Material
Aluminium Die Cast

Heatsink
Passive Cooled Aluminium

Finish
White Powder Coated

IP Rating
IP-20

Physical

Diameter
175mm

Cutout Diameter
167mm

Recessed Depth
55mm

Light Technology

Binning
3 step MacAdam

LED Life Time
> 50, 000 Hours

Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Optics

Secondary Optics
Diffused

Beam Direction
Non Adjustable

Electrical System

Input Voltage
220V-240V AC/50Hz

Input Power
22w

Power Factor
>0.95

ATHD
<20%

Driver
Fulham (Constant -
Current Led Driver)

Controls

Standard
Switchable On/Off

Optional
Phase Cut / Analog / Dali Dimming

CCT Tunable
Available on Request

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SR-077

LED Down Light Series
Ceiling Recessed Non Adjustable

SR - 077 22w

LED Fitted

Bridgelux LED 40Vdc/500mA

Co-Related Colour Temperature

3000K 4000K 6500K

Delivered Lumens

1320

Efficacy (System - lm/watt)

60

Beam Angle

110°

LED Power Watts

20

System Power Watts

22

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Opp Hdfc Bank , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com