


SRLED LIGHTS
www.srledlights.com

SR-123

LED Down Light Series
Ceiling Recessed non Adjustable

Specifications

Product Reference

Model No
SR-123
Installation Type
Recessed
Beam Direction
Non Adjustable

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50,000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
Diffused
Beam Direction
Non Adjustable

Physical

Diameter
155mm
Cutout Diameter
147mm
Recessed Depth
35mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
18W
Power Factor
>0.95
ATHD
<20%
Driver
Fulham (Constant -
Current Led Driver)

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SR-123

LED Down Light Series
Ceiling Recessed non Adjustable

SR - 123 18w

LED Fitted

Bridgelux Smd Led 40Vdc/400mA

Co-Related Colour Temperature

3000K 4000K 6500K

Delivered Lumens

1170

Efficacy (System - lm/watt)

65

Beam Angle

110°

LED Power Watts

16

System Power Watts

18

S.R.Industries
GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,
Opp Hdfc Bank , I.B.Patel Road ,
Goregaon (E), Mumbai - 400063.
Email Id : sales@srledlights.com
Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com