



Specifications

Product Reference

Model No
SR-124
Installation Type
Recessed
Beam Direction
350°adjustable

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
Optical Lens
Beam Direction
350°adjustable

Physical

Diameter
59mm
Cutout Diameter
65mm
Recessed Depth
34mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
10W
Power Factor
>0.95
ATHD
<20%
Driver
Fulham (Constant -
Current Led Driver)



SR

LED LIGHTS
www.srledlights.com

SR-124

LED down Light Series
Ceiling Recessed Adjustable

SR - 124 10w

LED Fitted

CREE COB LED 36Vdc/250mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

900

Efficacy (System - lm/watt)

90

Beam Angle

36°

LED Power Watts

9

System Power Watts

10

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Opp. Hdfc Bank , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com