

SRLED LIGHTS
www.srledlights.com

SR-070

LED Zoom Light Series
Ceiling Recessed Adjustable

Specifications

Product Reference

Model No
SR-070
Installation Type
Recessed
Beam Direction
Adjustable

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50,000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming
CCT Tunable
Available on Request

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
Metalized Reflector
Beam Direction
Adjustable

Physical

Diameter
145mm
Cutout Diameter
139mm
Recessed Depth
147mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
30W
Power Factor
>0.95
ATHD
<20%
Driver
Fulham (Constant -
Current Led Driver)

SRLED LIGHTS
www.srledlights.com



SR

LED LIGHTS
www.srledlights.com

SR-070

LED Zoom Light Series
Ceiling Recessed Adjustable

SR - 070 30w

LED Fitted

CREE COB LED 36Vdc/700mA

Co-Related Colour Temperature

2700K 3000K 3500K 4000K 5000K 6500K

Delivered Lumens

3000

Efficacy (System - lm/watt)

100

Beam Angle

15° / 24° / 38°

LED Power Watts

26

System Power Watts

30

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Opp Hdfc Bank , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com