



Specifications

Product Reference

Model No
SR-240
Installation Type
Recessed
Beam Direction
Non Adjustable

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI80 as standard/ CRI90 on Request

Controls

Standard
Switchable On/Off

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Optics

Secondary Optics
Metalized Reflector
Beam Direction
Non Adjustable

Physical

Diameter
45mm x 46mm
Cutout Diameter
39mm x 39mm
Recessed Depth
42mm

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
2.5w
Power Factor
>0.95
ATHD
<20%
Driver
Philips (Constant -
Current Led Driver)



SR

LED LIGHTS
www.srledlights.com

SR-240

LED leaser Light Series
Ceiling Recessed Non Adjustable

SR - 240 2.5w

LED Fitted

Bridgelux 5050 Smd Led 6Vdc/300mA

Co-Related Colour Temperature

3000K 4000K 6500K

Delivered Lumens

225

Efficacy (System - lm/watt)

90

Beam Angle

80°

LED Power Watts

1.8

System Power Watts

2.5

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Opp Hdfc Bank , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com