


Specifications

Product Reference

Model No
SRE-099
Installation Type
Wall surface Mounted
Beam Direction
Adjustable - Asymmetric

Construction & Materials

Housing Material
Aluminium Die Cast
Heatsink
Passive Cooled Aluminium
Finish
White Powder Coated
IP Rating
IP-20

Physical

outer trim
150mm
length
150mm
height
25mm

Light Technology

Binning
3 step MacAdam
LED Life Time
> 50, 000 Hours
Colour Rendering CRI
CRI90

Optics

Secondary Optics
Optical Lens
Beam Direction
Adjustable - Asymmetric

Electrical System

Input Voltage
220V-240V AC/50Hz
Input Power
21w
Power Factor
>0.95
ATHD
<20%
Driver
Philips (Constant -
Current Led Driver)

Controls

Standard
Switchable On/Off
Optional
Phase Cut / Analog / Dali Dimming (Driver Location Remote)
CCT Tunable
Not Available



SR

LED LIGHTS
www.srledlights.com

SRE-099

Led Up Lightr Series
Wall Up Lighter Adjustable

SRE-099 - 21w

LED Fitted

Bridgelux 5050 Smd Led 36Vdc/500mA

Co-Related Colour Temperature

3000K 4000K

Delivered Lumens

1470

Efficacy (System - lm/watt)

70

Beam Angle

Asymmetric

LED Power Watts

18

System Power Watts

21

S.R.Industries

GalaNo. 1 & 2, 1st Floor , Geeta Industrial Estate ,

Opp Hdfc Bank , I.B.Patel Road ,

Goregaon (E), Mumbai - 400063.

Email Id : sales@srledlights.com

Tel.No : 9137899504



SR

LED LIGHTS
www.srledlights.com